

Shenzhen XTAR Electronics Co., Ltd

XTAR Technology LLC


XTAR®
China's Got Quality!


XTAR® Product E-catalogue V1606



Интернет-магазин светодиодных фонарей

CONTENT

✓ Flashlight

- [Diving Series](#)
- [Search & Tactical Series](#)
- [Sport Series](#)
- [EDC Series](#)
- [Headlamps](#)


✓ Charger

- [1 slot](#)
- [2 slots](#)
- [4 slots](#)

✓ Battery

- [For Electronic cigarette](#)
- [For Flashlight/Camera/Medical Devices](#)

✓ Accessory



Flashlight . Diving Series



D35

- 3* Cree XM-L2 U2
- Max 2800 lumens
- Max 78500cd intensity
- 560m beam throw
- 100m waterproof
- 3* 18650/18700
- High-Mid-Low-Strobe mode
- Magnetic dimmer switch

- Cree XM-L2 U3
- Max 1100 lumens
- Max 22500cd intensity
- 300m beam throw
- 100m waterproof
- 1* 18650/18700/26650
- High-Mid-Low-Strobe mode
- Magnetic pressure switch

D26



Flashlight . Diving Series



D06


- Cree XM-L2 U2
- Max 900 lumens
- Max 23500cd
- 306m
- 100m waterproof
- 1* 18650/18700
- Low-High stepless mode
- Magnetic stepless dimming switch

Flashlight . Search & Tactical Series



TZ20 Platoon

- Cree XM-L2 U2
- Max 840 lumens
- Max 10000cd intensity
- 300m beam throw
- IPX8 waterproof
- 1* 18650/18700/17670
- High-Mid-Low-Strobe-SOS mode
- DIY Function
- Tactical tail cap switch



Flashlight . Sport Series




New
Arrival!

- Cree XP-G2 S2
- 60~450 lumens
- Max 13850cd intensity
- 235m beam throw
- IPX8 waterproof
- 1* 18650/18700
- Built-in charging system, 1A charging battery
- High-Low mode
- Tactical tailcap switch



RC1
Darkwalker



Flashlight . Sport Series



R30

- Cree XM-L2 U2
- Max 1000 lumens
- Max 18500cd intensity
- 272m beam throw
- IPX8 waterproof
- 1* 18650/18700
- Power indicator, rechargeable
- Turbo-High-Mid-Low-Strobe-SOS mode
- Side button switch




Flashlight . Sport Series



B20 Pilot II

- Cree XM-L2 U3
- Max 1100 lumens
- Max 13225cd intensity
- 230m beam throw
- IPX8 waterproof
- 1* 18650/18700/17670
- Turbo-High-Mid-Low-Signal mode
- Tactical tail cap switch



Flashlight . Headlamp Series



H3 Warboy (Cool White)

- Cree XM-L2 U3
- 5 Modes
- 1000 /400/200/70/1 lumens
- Max 6200cd Intensity
- Duration 2.9h~30ds
- Max 157m beam throw
- IPX8 Waterproof
- 1*18650 battery
- Clicky switch

Flashlight . Headlamp Series



New
Arrival!



H3W

Warboy-W (Warm White)


- XM-L2 U2
- 950/400/200/70/1 lumens
- 50000h Lifespan
- Duration 2.9h~30ds
- Five selectable brightness levels.
- Max 145m beam throw
- IPX8 waterproof
- 1*18650 battery
- Clicky switch

Flashlight . Headlamp Series



MOON RC2

- Samsung LED, Low Heat ,Long Lifespan
- Moonlight-Low-Medium-High-Strobe mode.
- 3/30/60/120/Lumens
- 1 built-in 18650 2200mAh Li-ion battery
- USB charging port
- Easy to stand, anti-roll
- IPX6 Waterproof
- Battery Power Indicator: Green-Red-Flashing Red
- Safe to use while charging




Flashlight . EDC Series



- 5 lumens
- Button cell battery
- Customized logo
- Press switch on
- 10g
- OEM

XPK Keychain
light



Charger . 2 slots



New Arrival!

Spec	SV2 Rocket
Apply to	3.6V/3.7V 10440~32650 Li-ion/ IMR /INR/ ICR AAAA/AAA/AA/A/SC/C/D/Ni-MH/Ni-CD
Input power	12.0V DC/2.0A
Charging current	0.25A/0.5A/1.0A/2.0A optional
Cut-off Voltage	4.20 ± 0.05V(Li-ion) 1.45 ± 0.1V(Ni-MH/Ni-Cd)
Unique features	<ul style="list-style-type: none">•Fast-charging Charger with LCD•4 optional charging currents•TC-CC-CV•Display charging status precisely•0V activation•Short circuit protection•Red-Green LED indicator



USB Charger . 6 ports



New
Arrival!



Spec	U1 (Six-U)
Apply to	Smartphone, Tablets, E-cigs, Electronic Watches, USB Battery Chargers, MP3/MP4, Bluetooth Headset and more...
Input power	100-240V~ 1.05A 50-60Hz
Output Power	45W 5V 9A (each 2.4A max)
Size	100(L) * 80(W) *30(H) mm
Unique features	High Compatibility - Compatible with any USB devices; 100-240V suitable for international use Intelligent Ports - Built-in smart Microchip detects your device and chooses its fastest possible charge current intelligently The Fastest Charging Speed - Nickel plated ports + gold plated contacts + Voltage Compensation Technique- Max 2.4A a port





Charger . 1 slot


Spec	MC1	MC1 Plus	ANT MC1 Plus New~
Apply to	3.6V/3.7V 10440~26650 Li-ion	3.6V/3.7V 10440~26650 Li-ion	3.6V/3.7V 10440~26650 Li-ion
Input power	DC 5.0V 500mA	DC 5.0V 1.0A	DC 5.0V 1.0A
Charging current	0.5A	0.5A/1A	0.5A/1A
Cut-off Voltage	4.2V \pm 0.05V	4.2V \pm 0.05V	4.2V \pm 0.05V
Unique features	<ul style="list-style-type: none">•0V activation•Portable size•Low heat control•Short circuit protection•Red-Green LED indicator	<ul style="list-style-type: none">•Auto detect battery and select charging current•0V activation•Low heat control•Short circuit protection•Red-Green LED indicator	<ul style="list-style-type: none">•Auto detect battery and select charging current, show in the surface(0.5A/1.0A)•Battery charging status display•0V activation•Low heat control•Short circuit protection



Charger . 2 slots



Spec	MC2	VP2
Apply to	3.6V/3.7V 14500~18700 Li-ion	3.2V/3.6V/3.8V 10440~26650 Li-ion
Input power	DC 5.0V 1.0A	DC 12.0V 1.0A
Charging current	0.50A max	0.25A/0.5A/1A optional
Cut-off Voltage	4.2V \pm 0.05V	3.6V \pm 0.05V(3.0V/3.2V battery) 4.2V \pm 0.05V(3.6V/3.7V battery) 4.35V \pm 0.05V(3.8V battery)
Unique features	<ul style="list-style-type: none"> •Self adjust charging current according to input power •0V activation •Low heat control •Short circuit protection •Red-Green LED indicator 	<ul style="list-style-type: none"> •3 optional charging currents and voltages •USB output 5V/1A •Display charging status precisely •0V activation •Short circuit protection •Red-Green LED indicator



Charger . 2 slots



Spec	VC2	VC2 Plus
Apply to	3.6V/3.7V 10440~26650 Li-ion	3.2V/3.7V 10440~36650 Li-ion/IMR/INR/ICR/ AAAA/AAA/AA/A/SC/C/D Ni-MH/Ni-CD
Input power	DC 5.0V 1.0A	DC 5.0V 2.1A
Charging current	0.5A	0.5A/1A optional
Cut-off Voltage	4.2V \pm 0.05V	4.2V \pm 0.05V(Lithium battery) 1.4V \pm 0.1V(Ni-MH battery) 3.2V \pm 0.2V(Over Discharge Protection Voltage)
Unique features	<ul style="list-style-type: none"> •Display how much capacity charged •Self-adjust charging current according to input power •USB input cord •0V activation •Short circuit protection 	<ul style="list-style-type: none"> •Battery fully charged countdown timer •USB output 5V/1A •Battery input power icon and percentage display •USB output battery power percentage display •Batteries and device charging at the same time •0V activation •Short circuit protection •Red-Green LED indicator





Charger . 4 slots

Spec	VC4	VP4	XP4
Apply to	3.6V/3.7V 10440~32650 Li-ion; AAAA/AAA/AA/A/SC/C/D Ni- MH/Ni-Cd	3.6V/3.7V 10440~26650 Li- ion	3.6V/3.7V 10440~26650 Li-ion AAA/AA/A/SC/C Ni-MH/Ni-Cd
Input power	DC 5.0V 2.1A	DC 12.0V 1.0A	DC 12.0V 2.0A
Charging current	1A max(CH1&4) 0.5A max(CH2&3)	0.25A/0.5A/1A optional	0.25A/0.5A/1A optional
Cut-off Voltage	4.2V \pm 0.05V(Li-ion) 1.45 \pm 0.1V(Ni-MH/Ni-Cd)	4.2V \pm 0.05V	4.2V \pm 0.05V(Li-ion) 1.4V \pm 0.05V(Ni-MH/Ni-Cd)
Unique features	<ul style="list-style-type: none">•Compatible with Ni-MH/Ni-Cd•Display how much capacity charged•Self-adjust charging current•0V activation•Short circuit protection•Red-Green LED indicator	<ul style="list-style-type: none">•Display battery voltage and power bar precisely•3 optional charging currents•0V activation•Low heat control•Short circuit protection	<ul style="list-style-type: none">•USB output 5V 1A•3 optional charging currents•Compatible with Ni-MH/Ni-Cd•0V activation•Low heat control•Short circuit protection•Red-Green LED indicator





Battery . For Electronic cigarette


Size & Capacity	Description
18650 2500mAh	Samsung INR18650-25R, 3.6V unprotected, 20A high drain
18350 850mAh	3.7V IMR unprotected, button top, 4.25A high drain
26650 3200mAh Clearance	3.7V IMR battery, flat top, 35A high drain
18650 2900mAh Clearance	Panasonic NCR18650PF, 3.6V unprotected, button top, 10A high drain



Battery . For Flashlight/Camera/Medical Devices



Size & Capacity	Description
26650 5000mAh new~	Domestic Cell, 3.6V protected, button top, 8A high drain
18650 3400mAh	SANYO NCR18650BF, 3.6V protected, button top, 4.87A high drain
18650 3100mAh	Panasonic NCR18650A, 3.7V protected, button top, 3.54A high drain
18650 2600mAh	Samsung ICR18650-26F, 3.7V protected, button top, 5.2A high drain
18700 2600mAh	SANYO UR18650FM, 3.7V protected, button top, 4.5A high drain
18650 2200mAh	3.7V protected, button top, 2.2A high drain
14500 800mAh	3.7V protected, button top, 1.6A high drain
16340 600mAh/16340 650mAh	3.6V protected, button top, 1.2A high drain
CR123A 1400mAh	3V unprotected, button top, non rechargeable
18650 3200mAh	Samsung ICR18650-32A, 3.75V unprotected raw cell, 6.4A high drain



Accessory



VI01

USB Detector

Battery Case



Spacer

GR1

Lubrication oil for flashlight

HDL1

Flashlight Handle for D35 & S1

