

# 2019/2020 Catalo 90 C





Manufacturer: Ningbo Sunree Outdoor Products Co.,Ltd. Address:Building2,Hutang Industrial Park, Zhouxiang Town,Cixi,Zhejiang,China



#### 山力士创始人兼首席设计师毛焕军先生

执着的户外爱好者又是资深的产品设计师。热爱户外、崇尚自由,十多年注塑模具及工业设计从 业经验,酷爱探洞、登山、单车、摩旅等各种户外运动,坚信户外装备设计灵感源自户外运动,将自己的体会 和灵感融入到产品中,让设计作品充满"自然气息"。

2006年,凭借多年的户外实践和设计经验,创立了SUNREE户外运动灯具品牌,跻身国内户外运动照明领军品牌行列。SUNREE凭借其出色的工业设计和良好是市场信誉,得到了户外消费者的一致认同,并屡次获得亚洲户外产业大奖、中国制作之美优秀奖、和丰工业设计大奖、中国设计红星奖以及德国慕尼黑ISPO亚洲奖等国内外相关奖项。

自2010年之后,SUNREE开始走向国际市场,于2018年正式进入工具市场,并在相关领域取得了丰硕的业绩。

SUNREE Founder and Chief Designer: Mr. Mao

Be keen on Outdoor Sports. Love Outdoors, Advocate Freedom!

More than 20 years of experience in injection mold and design. We firmly believe that good design comes from life. Mr. Mao enjoys caving, climbing, riding, motorcycling, and other outdoor sports, also integrate these experience and inspiration into products.

Founded in 2006, SUNREE quickly became one of the leading brands of Outdoor Lighting. We won a high reputation from customers, also gained a lot of awards, such as ISPO Award, The beauty of making in China, Hefeng Industrial Design Award, China Design Red Star Award, etc.

Since 2010, SUNREE has begun to enter into the international market. Later, we entered into the tool light market from 2018. Start SUNREE brand sales, also cooperate with a lot of famous brand, offer OEM, and ODM service.

标识	标识说明 Identification
标示该产品采用轻	量化设计
This pattern indic	ates the product employs light-weight design.
标示该产品内置光	源为CREE大功率LED
This pattern indic	ates the product equips Cree LED as light source.
标示该产品内置光	源为国产高亮白光LED
This pattern indic	ates the product equips Chinese LED as light source.
标示该产品内置光源为COB	
This pattern indic	ates the product equips COB as light source.
1—————————————————————————————————————	和泛光两组光源
This pattern indic	ates the product adopts focus light /floodlight
标示该产品有主灯白光和红光两组光源	
This pattern indicates the product adopts white light/re	ates the product adopts white light/red light as light sources.
标示该产品有采用两颗大功率LED	
This pattern indic	ates the product equips 2*high-power LED as light sources.
标示该产品也可以作为手电使用	作为手电使用
标示该产品也可以 This pattern indic	ates the product can be also used as flashlight.
标示该产品有远光,泛光,红光三组光源   This pattern indicates the product adopts focus light / floodlight / red light	
This pattern indic	ates the product with magnet.
标示该产品有挥手感应功	感应功能
This pattern indic	ates the product with sensor function
● ☆ 标示该产品可适应的使用温度	
This pattern indic	ates the product adpats to the environment
标示该产品完全防雨2	雨水或一般生活防水
This pattern indic	ates the product can be protected from rain or general life waterproof
标示该产品采用标准USB充放电接口设计	
USB This pattern indic	ates the product employs standard USB charge-discharge design.
标示该产品采用标	准DC充电接口设计



重量:1450.5g 包装:彩盒包装 Max: 3000LM Running Time: 57H (Mode: Low) Battery:11.1V/5200mAh LED:COB(2700K/6500K) Mode:Dimming Mode DC Input:20V/1.2A USB Output:5V/2A Charging Time: 4H IP65 Mainly material: ABS, PA66-GF30, Aluminum Size:243x236x125mm Weight:1450.5g Package:Colorbox

最大流明:3000流明 最大续航时间:57小时(节能模式) 电池:11.1V/5200mAh 灯珠:COB双色温(2700K/6500K) 照明模式:无极调光 DC输入:20V/1.2A USB输出:5V/2A 充电时间:4小时 防尘防水等级:IP65 主要材质:ABS/PA66-GF30/铝 外观尺寸:243x236x125mm

**V3000** 

3000 LM

170°

色温调节开关 亮度调节开关 Color Brightness temperature switch 三角架支撑孔 Can be adapted to a tripod Интернет-магазин светод

吸磁设计,内置磁铁

Magnet





switch





吸磁设计 Magnet 最大流明:1000流明 最大续航时间:90小时(节能模式) 电池:3.7V/4200mAh 灯珠:2\*CREE LED (6500K) 照明模式:模式1:中亮→高亮→低亮→熄灭(远光模式) 模式2:高亮→低亮→熄灭(泛光模式) (模式1与模式2长按切换,任一工作状态工作3秒后轻 按可直接关闭) USB输入:5V/2A 防尘防水等级:IP65 主要材质:ABS/包胶/铝 外观尺寸:85x184x54mm(带底座) 76x168x54mm(不带底座) 重量:252g(带底座)/222g(不带底座) 包装:彩盒包装 Max: 1000LM Running Time:90H (Mode: Low/Focus light) Battery:3.7V/4200mAh

LED:2\*CREE LED (6500K)

USB Input: 5V/2A

Package:Colorbox

IP65

Mode2:High→Low→OFF (Floodlight)

Mainly material: ABS/Rubber cover/Aluminum

Size:85x184x54mm (Basement) 76x168x54mm (Basement excluded)

可拆卸快挂设计

140°

Detachable hanging design

**L1000** 1000 LM TPYE C接口 Type C Interface \*\*\* CREE -20-60°C TPYE-C Mode:Mode1:Middle→High→Low→OFF (Focus light) 充电触电 Charging contact (Press and hold the button to exchange mode 1 and mode 2. Press button to turn off the light if no operation exceed 3s) 充电底座 Charging basement Weight:252g(Basement)/222g(Basement excluded)



最大流明:800流明 最大续航时间:90小时(节能模式) 电池:3.7V/4200mAh 灯珠:6500K白光灯珠 照明模式:模式1:中亮→高亮→低亮→熄灭 USB输入:5V/2A 防尘防水等级:IP65 主要材质:ABS/包胶/铝 外观尺寸:134x184x53mm(带底座) 125x168x36mm(不带底座) 重量:232g(带底座)/202g(不带底座) 包装:彩盒包装 Max: 800LM Running Time:90H (Mode: Low) Battery :3.7V/4200mAh LED: White LED (6500K)  ${\tt Mode:Mode1:Middle \rightarrow High \rightarrow Low \rightarrow OFF}$ USB Input:5V/2A IP65 Mainly material: ABS/Rubber cover/Aluminum Size:134x184x53mm (Basement) 125x168x36mm (Basement excluded) Weight:232g(Basement)/202g(Basement excluded) Package:Color box \*\* CREE

-20-60°C



可拆卸快挂设计

140°

Detachable hanging design

吸磁设计



防水等级:IPX5

重量:180g 包装:彩盒包装

Max: 380LM

Battery: 3.7V/2600mAh

USB Input:5V/1A

Weight:180g

Package:Colorbox

IPX5

Charging Time: 3.7h

Mainly material: ABS/PA66-GF30

Size:55x123x32mm(Folded size)

55x215x32mm(Expand size)

主要材质:ABS/PA66-GF30

外观尺寸:55x123x32mm(折叠状态)

Running Time: 102H(Mode: Low/COB)

LED:COB(6500K)+White LED (6500K)

55x215x32mm(展开状态)

фонарей

Mode:Mode1:Middle→High→Low→→OFF(COB Floodlight)

Mode2:High→Middle→OFF(Top Flashlight Mode)

(Press and hold the button to exchange mode 1 and mode 2.

Press button to turn off the light if no operation exceed 3s)

# 380 LM 240°

**V380** 







165°



#### 













最大流明:220流明 最大续航时间:260小时(节能模式) 电池:3\*AA 灯珠:4500K大功率白光LED+6500K大功率白光LED+红光LED 照明模式:模式1:中亮→高亮→低亮→熄灭(泛光模式) 模式2:中亮(远)→高亮(远)→高亮(红)→频闪(红)→熄灭 (模式1与模式2长按切换,任一工作状态工作3秒后轻按可直接关闭) 防水等级:IPX5 主要材质:ABS/PC 外观尺寸:80x80x47mm 重量:99g(不含电池) 包装:吸塑包装 Max: 220LM Running Time: 260H (Mode: Low/Floodlight) Battery:3\*AA LED:White LED (4500K) +White LED(6500K)+Red LED Mode:Mode1:Middle $\rightarrow$ High $\rightarrow$ Low $\rightarrow$ OFF (Floodlight) Mode2:Middle (Focus light) → High (Focus light) → High (Red) →Strobe (Red) →OFF (Press and hold the button to exchange mode 1 and mode 2. Press button to turn off the light if no operation exceed 3s) IPX5 Mainly material: ABS/PC Size:80x80x47mm Weight:99g (Without battery)

最大流明:200流明 最大续航时间:100小时(节能模式) 电池:4\*AA 灯珠:6500K大功率白光灯珠 照明模式:模式1:高亮→中亮→低亮→频闪→SOS→熄灭 防水等级:IPX6 主要材质:ABS/PC 外观尺寸:66x66x134mm(收纳状态) 66x66x194mm(展开状态) 重量:146g(不含电池) 包装:彩盒包装 Max: 200LM Running Time: 100H (Mode: Low) Battery:4\*AA LED: White LED (6500K)  $\mathsf{Mode}:\mathsf{Mode}1:\mathsf{High}{\rightarrow}\mathsf{Middle}{\rightarrow}\mathsf{Low}{\rightarrow}\mathsf{Strobe}{\rightarrow}\mathsf{SOS}{\rightarrow}\mathsf{OFF}$ IPX6 Mainly material: ABS/PC Size:66x66x134mm(Folded size) 66x66x194mm (Expand size) Weight: 146g (Without battery) Package:Color box



**C190** 

**C200** 

200 LM



# Интернет-магазин светодиодных фонарей

最大流明:390流明 最大续航时间:221小时(节能模式) 电池:8400mAh 灯珠:4500K大功率LED 照明模式:模式1:中亮→高亮→低亮→频闪→熄灭 USB充电:5V/1.5A USB充电时间:8小时 防水等级:IPX5 主要材质:ABS/PC/铝合金 外观尺寸:70x70x83mm 重量:315g 包装:彩盒包装 Max: 390LM Running Time:221H (Mode:Low) Battery:8400,mAh LED:White LED (4500K)  ${\tt Mode:Mode1:Middle \rightarrow High \rightarrow Low \rightarrow Strobe \rightarrow OFF}$ USB Input:5V/1.5A Charging Time: 8h IPX5 Mainly material: ABS/PC/Aluminum Size:70x70x83mm Weight:315g Package:Color box

Package: Blister Package

最大流明:190流明 最大续航时间:130小时(节能模式) 电池:3\*AAA 灯珠:4500K大功率白光灯珠 照明模式:模式1:中亮→高亮→低亮→频闪→熄灭 防水等级:IPX5 主要材质:ABS/PC 外观尺寸:52x52x114mm(收纳状态) 52x52x164mm(展开状态) 重量:84g(不含电池) 包装:彩盒包装 Max: 190LM Running Time: 130H(Mode: Low) Battery : 3\*AAA LED:White LED (4500K) Mode:Mode1:Middle→High→Low→Strobe→OFF IPX5 Mainly material: ABS/PC Size: 52x52x114mm(Folded size) 52x52x164mm (Expand size) Weight: 84g (Without battery) Package:Color box

感应开关 Sensor switch

最大流明:330流明 **MUYE2** 最大续航时间:96小时(节能模式) 电池:1\*18650(测试用1节带保护板的2600mAh 18650锂电池) 灯珠:CREE LED (6500K) 330 LM 照明模式:模式1:中亮→高亮→低亮→熄灭 轻按感应键,开启感应模式 感应距离:≤15厘米 SURGE USB充电:5V/1A 充电时间:3.5小时 防水等级:IPX5 主要材质:ABS/PC 外观尺寸:65x32x35mm SUREI: 重量:115g(不含电池) Max: 330LM Running Time:96H (Mode:Low) Battery: 1\*18650 (Tested by 1\*2600mAh LI-battery with protection board) LED:White LED (6500K) Mode:Mode1:Middle→High→Low→SOS→OFF(Focus light) 感应装置 调焦旋钮 Sensor Press sensor button to sensor mode zoomable switch Sensing distance:≤15cm USB Input:5V/1A Charging Time: 3.5h IPX5 Mainly material: ABS/PC 电量指示灯 Size:65x32x35mm Power indicator Weight:115g(Without battery) Package:Color box CREE LED

### етод Рескаде: Color box Х ФОНАРЕЙ

重量:93.5g 包装:彩盒包装 Max: 440LM Running Time: 70H(Mode: Low) Battery: 1800mAh LED: CREE LED (6500K) +White LED (6 Mode: Mode1:Middle (Focus light)→ Extremely bright (Focu Low(Floodlight)→OFF, Press sensor button to sensor mode Sensing distance: <15cm USB Input:SV/IA Charging Time: 2.3h IPX5 Mainly material: ABS/PC Size: 60x39x42mm Weight: 93.5g

最大流明:440流明 最大续航时间:70小时(节能模式) 电池:1800mAh 灯珠:CREE LED (6500K)+White LED (6500K) 照明模式:模式1:中亮(远光)→高亮(远光)→极亮(远光+泛光) →高亮(泛光)→低亮(泛光)→熄灭 轻按感应键,开启感应模式 感应距离:≤15厘米 USB充电:5V/1A USB充电时间:2.3小时 防水等级:IPX5 主要材质:ABS/PC 外观尺寸:60x39x42mm 重量:93.5g LED: CREE LED (6500K) +White LED (6500K) Mode: Mode1: Middle (Focus light) → High (Focus light) → Extremely bright (Focus light+Floodlight) → High(Floodlight)→ Low(Floodlight)→OFF



感应开关 Sensor switch











散热设计 Heat Emission Design



双开关按钮 Two Switches









#### 电池:3\*AAA 灯珠:COB双色(红/白) 照明模式:模式1:高亮→中亮→低亮→频闪 →熄灭(白光模式) 模式2:高亮→频闪→熄灭(红光模式) 防水等级:IPX6 主要材质:ABS/PC 外观尺寸:63x35x45mm 重量:59g(不含电池) 包装:彩盒包装 Max: 320LM Running Time:97H (Mode: Low/White) Battery: 3\*AAA LED:COB (Red/White) Mode:Mode1:High→Middle→Low→Strobe→OFF(White light) $\mathsf{Mode1}:\mathsf{High}{\rightarrow}\mathsf{Strobe}{\rightarrow}\mathsf{OFF}(\mathsf{Red}\:\mathsf{light})$ IPX6 Mainly material: ABS/PC Size:63x35x45mm Weight:59g(Without battery) Package:Color box Интернет-магазин светод

最大流明:300流明

电池:3\*AAA

防水等级:IPX6

包装:彩盒包装

Battery:3\*AAA

IPX6

Max:300LM

主要材质:ABS/PC

外观尺寸:60x35x44mm

Mainly material: ABS/PC

Size:60x35x44mm

Package:Color box

Weight:67.5g

重量:67.5g(不含电池)

最大续航时间:115小时(节能模式)

灯珠:CREE LED(6500K)+1\*White LED(6500K)+1\*Red LED

高亮(泛)→低亮(泛)→熄灭

模式2:高亮→频闪→SOS→熄灭(红光模式)

照明模式:模式1:中亮(远)→高亮(远)→高亮(远+泛)→

Running Time:115H(Mode: Low/Floodlight)

LED: CREE LED(6500K)+1\*White LED(6500K)+1\*Red LED

Mode: Mode1: Middle (Focus light) → High (Focus light) →

Mode2:High→Strobe→SOS→OFF(Red light)

Low (Floodlight) → OFF

High (Focus light+Floodlight) → High (Floodlight) →

最大流明:320流明 最大续航时间:97小时(节能模式)

> 最大流明:55流明 最大续航时间:29小时(节能模式) 电池:500mAh 灯珠:4500K白光灯珠 照明模式:模式1:高亮→低亮→熄灭 模式2:低亮→熄灭(感应模式) (长按按键开启感应低亮模式) 感应距离:7-15厘米 USB充电:5V/0.25A USB充电时间:2.5小时 防水等级:IPX5 主要材质:ABS/PC 外观尺寸:48x36x26mm 重量:25g 包装:吸塑包装 Max:55LM Running Time: 29H(Mode: Low) Battery: 500mAh LED: White LED(4500K) Mode:Mode1:High→Low→OFF Mode2:Low→OFF(Sensor mode) Press and hold button to change lighting mode Sensing distance: 7-15cm USB Input: 5V/0.25A Charging Time: 2.5H IPX5 Mainly material: ABS/PC Size:48x36x26mm Weight:25g Package: Bilster Package

最大流明:100流明 最大续航时间:27小时(节能模式) 电池:500mAh 灯珠:COB双色(红/白) 照明模式:模式1:中亮(远)→高亮(远)→低亮(远)→高亮(红) →频闪(红)→熄灭 (轻按感应键,开启感应模式) 感应距离:7-15厘米 USB充电:5V/0.5A USB充电时间:1.5小时 防水等级:IPX5 主要材质:ABS/PC 外观尺寸:60x50.5x22.4mm 重量:38.5g 包装:吸塑包装 Max:100LM Running Time: 27H (Mode: Low Battery: 500mAh LED:COB(Red/White) Mode: Midlle $\rightarrow$ High $\rightarrow$ Low $\rightarrow$ High(Red) $\rightarrow$ Strobe(Red) $\rightarrow$ OFF Press sensor button to sensor mode Sensing distance:7-15cm USB Input: 5V/0.5A Charging Time: 1.5H IPX5 Mainly material : ABS/PC Size:60x50.5x22.4mm Weight: 38.5g Package: Bilster Package фонарей



190°

SUNTERS

感应装置

Sensor



**H100** 

100 LM

**H50** 

55 LM





13

## **iFishing-Li** 230 LM





# iFishing 225 LM



最大流明:230流明 最大续航时间:110小时(节能模式) 电池:1800mAh 灯珠:CREE LED(4500K) 照明模式:模式1:中亮→高亮→低亮→熄灭(远光模式) 模式2:高亮→熄灭(感应模式) (关闭下长按进入感应模式) 感应距离:7-15cm USB充电:5V/1A USB充电时间:2.8小时 防水等级:IPX5 主要材质:ABS/PC 外观尺寸:63x37x42mm 重量:89g 包装:彩盒包装 Max:230LM Running Time: 110H(Mode: Low) Battery: 1800mAh LED: CREE LED(4500K)  $Mode:Mode1:Middle \rightarrow High \rightarrow Low \rightarrow OFF(Focus \ light)$ Mode2:High→OFF(Sensor mode) Press and hold button to chage lighting mode Sensing distance: 7-15cm USB Input: 5V/1A Charging Time: 2.8H IPX5 Mainly material: ABS/PC Size:63x37x42mm

Weight:89g

电池:3\*AAA

Package:Color box

灯珠:CREE LED(4500K)

最大续航时间:120小时(节能模式)

照明模式:模式1:中亮→高亮→低亮→熄灭(远光模式) 模式2:高亮→熄灭(感应模式)

最大流明:200流明 最大续航时间:153小时(节能模式) 电池:1800mAh 灯珠:3\*6500K白光LED 照明模式:模式1:中亮→高亮→低亮→SOS→熄灭(远光模式) 模式2:高亮→低亮→频闪→熄灭(泛光模式) (模式1与模式2长按切换,任一工作状态工作3秒后轻按可直接关闭) USB充电:5V/1A USB充电时间:2.5小时 防水等级:IPX5 主要材质:ABS/PC 外观尺寸:60x45x30mm 重量:95g 包装:吸塑包装 Max:200LM Running Time: 153H(Mode:Low/Focus light) Battery:1800mAh LED: 3\*White LEDs (6500K) Mode:Mode1:Midlle→High→Low→SOS→OFF(Focus light)  $\mathsf{Mode2:High}{\rightarrow}\mathsf{Low}{\rightarrow}\mathsf{Strobe}{\rightarrow}\mathsf{OFF}(\mathsf{Floodlight})$ (Press and hold the button to exchange mode 1 and mode 2. Press button to turn off the light if no operation exceed 3s) USB Input: 5V/1A Charging Time: 2.5H Water resistance: IPX5 Mainly material: ABS/PC Size:60x45x30mm Weight:95g Package: Bilster Package







H200 195 LM





#### (关闭下长按进入感应模式) 感应距离:7-15cm 防水等级:IPX6 主要材质:ABS/PC 外观尺寸:63x37x42mm 重量:61g(不含电池) 包装:彩盒包装 Max:225LM Running Time: 120H(Mode: Low) Battery: 3\*AAA LED: CREE LED(4500K) Mode:Mode1:Middle→High→Low→OFF(Focus light)

**в**хжи:225жи СТ-Магазин сестодиодных оонарей

最大流明:195流明

最大续航时间:180小时(节能模式)

Mode2:High→OFF(Sensing) Press and hold button to enter into sensor mode when the light is off Sensing distance: 7-15cm IPX6 Mainly material: ABS/PC Size:63x37x42mm Weight:61g(Without battery) Package:Color box

电池:3\*AAA 灯珠:3\*6500K白光LED 照明模式:模式1:中亮→高亮→低亮→SOS→熄灭(远光模式) 模式2:高亮→低亮→频闪→熄灭(泛光模式) (模式1与模式2长按切换,任一工作状态工作3秒后轻按可直接关闭) 防水等级:IPX6 主要材质:ABS/PC 外观尺寸:60x45x30mm 重量:62g(不含电池) 包装:吸塑包装 Max:195LM Running Time: 190H (Mode: Low/Focus light) Battery: 3\*AAA LED:3\*White LEDs (6500K) Mode:Mode1:Midlle→High→Low→SOS→OFF(Focus light) Mode2:High→Low→Strobe→OFF(Floodlight) (Press and hold the button to exchange mode 1 and mode 2. Press button to turn off the light if no operation exceed 3s) IPX6 Mainly material: ABS/PC Size:60x45x30mm Weight:62g (Without battery) Package: Bilster Package















最大流明:700流明 最大续航时间:260小时(节能模式) 电池:2\*18650(测试用2节带保护板的2600mAh 18650电池) 灯珠:6500K大功率白光LED 照明模式:模式1:高亮→低亮→熄灭(无级调光) 防水等级:IPX5 主要材质:ABS/PC/铝合金 外观尺寸:71x37x42mm 重量:180g(不含电池) 包装:彩盒包装 Max:700LM Running Time: 260H(Mode: Low) Battery capacity: 2\*18650(Tested by 2\*2600mAh Li-battery with protection board) LED:White LED (6500K) Mode:Mode1:High→Low→OFF(Dimming Mode) IPX5 Mainly material: ABS/PC/Aluminum alloy Size:71x37x42mm Weight: 180g (Without battery) Package:Color box

最大流明:390流明

防水等级:IPX5

IPX5

主要材质:ABS/PC

外观尺寸:49x31x52mm 重量:141g(不含电池) 包装:彩盒包装 Max:390LM

LED:CREE LED (6500K/4500K)

Mainly material: ABS/PC Size: 49x31x52mm

Weight:141g (Without battery) Package:Color box

最大续航时间:140小时(节能模式)

灯珠:CREE LED(6500K/4500K)

电池:2\*18650(测试用2节带保护板的2600mAh 18650电池)

照明模式:模式1:中亮→高亮→低亮→SOS→熄灭(远光模式) 模式2:中亮→高亮→低亮→频闪→熄灭(泛光模式) (模式15模式2长按切换,任一工作状态工作3秒后轻按可直接关闭)

Running Time: 140H (Mode: Low/Floodlight)

Battery capacity:2x18650(Tested by 2\*2600mAh Li-battery with protection board)

Mode:Mode1:Middle→High→Low→SOS→OFF(Focus light) Mode2:Middle→High→Low→Strobe→OFF(Floodlight) (Press and hold the button to exchange mode 1 and mode 2. Press button to turn off the light if no operation exceed 3s)

Интернет-магазин светод

最大流明:40流明 最大续航时间:32小时(节能模式) 电池:120mAh 灯珠:6500K白光LED+红光LED 照明模式:模式1:中亮→高亮→低亮→熄灭(远光模式) 模式2:高亮→频闪→跑马灯→熄灭(红光模式) (模式1与模式2长按切换,任一工作状态工作3秒后轻按可直接关闭) 防水等级:IPX5 主要材质:ABS/PC 外观尺寸:26x20x56mm 重量:14g(不含电池) 包装:吸塑包装 Max:40LM Running Time: 32H (Mode: Low/Focus light) Battery: 120mAh LED:White LED (6500K) +Red LED Mode: Mode1: Middle→High→Low→OFF(Focus light) Mode2:High→Strobe→Marquee→OFF(Red light) (Press and hold the button to exchange mode 1 and mode 2. Press button to turn off the light if no operation exceed 3s) IPX5 Mainly material: ABS/PC Size:26x20x56mm X OOHapen Weight: 14g (Without battery) Package:Blister Package



Fun







**E-Charger** 易充 (高效能太阳能充电板) 10W

