

KUPIF®NAK-KZ

Интернет-магазин светодиодных фонарей

About us

WUBEN — an international brand casted for 38 years with ingenuity

Shenzhen ShengQi Lighting Technology Co., Ltd. is a lighting company with a history of 38 years. Headquartered in Qishi Town, Dongguan City, Guangdong Province, China, the company owns approximately 9,000 square meters of land. The self-built factory is about 15,000 square meters, with a team of more than 400 people, which is consisted of domestic and foreign professional R&D engineers, designers, production and sales personnel, and has advanced production and testing equipments, and is also equipped with the international standard test laboratory.


Adhering to the principles of design innovation, comfort and durability, WUBEN specializes in high-end LED flashlights R&D, designing and manufacturing. With high quality and excellent performance, WUBEN flashlights are well recognized by users and enthusiasts, and sell very well in many countries and regions, such as the United States, the United Kingdom, Germany, Australia, Russia, Poland, South Korea, Japan, South Africa, the Middle East, Southeast Asia.



▶ Icon illustration

YHE Output (1) Runtime Weight Dimension LED Type-C charging port Micro-USB charging port Intensity Beam distance Impact resistance m Waterproof level K Tint

► Tint illustration



KUPIF®NAR.KZ

Интернет-магазин светодиодных фонарей









Tactical Flashlight

- ▶ Utilized 1*CREE XP-L2 LED
- ► Powered by 1 pcs 18650 Li-ion battery, compatible with 2 pcs CR123A Lithium batteries
- ► Tactical and outdoor dual modes
- ► Ambidextrous tail switch design
- ► Instant Strobe
- Anti-vibration design
- ► Hard anodizing aircraft grade aluminum alloy

	FL1 Star	ndard	Turbo	High	Mid	Low	Strobe	SOS
	3114	1	200 \600 LM	260LM	10LM	1LM	1200LM	260LM
	<u>(</u>	5	+90mins	3.6h	84h	530h	/	/
	4	Z 1	140g/ 4.94oz (without battery) 190g/ 6.70oz (with battery)					
\	Imhahalad		144mm x 38mm 5.67in x 1.50in (L x D)					

1 x CREE XP-L2 LED

230m



















T20

Pistol Light

- ► Utilized 1*CREE XP-L2 LED
- ▶ Powered by 1 pcs CR123A Lithium battery
- Optional extensive tube
- ► Compatible with many pistols
- Quick assembly and disassembly
- ► Hard anodizing aircraft grade aluminum alloy

FL1 Standard	Constant on (1*CR123A)	Constant on (2*CR123A)	Strobe			
July 1	600 √350LM	1100 √600LM	1000LM			
(\subset)	3+90mins	3+180mins	/			
<u> </u>	96g/ 3.39oz (without battery) 112g/ 3.95oz (with battery)					
Imterledent	85mm x 34.5mm 3.35in x 1.36in (L x D)					

	1 x CREE
7	XP-L2 LEI
















08







H8

Hunting Flashlight

- ► Utilized 1*CREE XHP35 HI LED
- ► Powered by 2 pcs 18650 Li-ion batteries
- Hunting and outdoor dual modes
- ▶ 1000 meters max beam distance
- ► Optional red, green and blue filter set for hunting
- ► Hard anodizing aircraft grade aluminum alloy

FL1 Stand	lard High	Mid	Low	Eco	Strobe	SOS	
31/2	1800LM	500LM	130LM	5LM	1800LM	200LM	
()	3h	4.5h	18h	468h	/	/	
Δ] Δ	298g/ 10.5	298g/ 10.53oz (without battery) 395g/ 13.93oz (with battery)					
Imimimimi	250mm x (250mm x 63mm 9.84in x 2.48in (L x D)					

	1 x CREE
7	XHP35 HI LED



















H9

Zoomable Green Laser Flashlight

- Utilized 1*OSRAM 520nm green laser module
- ▶ Powered by 1 pcs 18650 Li-ion battery
- ▶ 10 mW output
- Zoomable design for both aiming and illuminating
- Anti-vibration design
- ► Hard anodizing aircraft grade aluminum alloy

FL1 Standard	Spot light	Flood light		
311/2	10mW	10mW		
(S)	6h	6h		
	1035m	108m		
	268000cd	2900cd		

128g/ 4.52oz (without battery) | 176g/ 6.21oz (with battery) 191mm x 35mm (L x D) 7.52in x 1.38in















T31

Multi Color Light Sources Flashlight

- Utilized 1*CREE XP-L white light LED, 1*CREE XP-E red light LED, 1*CREE XP-E green light LED and 1*CREE XP-E blue light LED
- ► Powered by 1 pcs 18650 Li-ion battery, compatible with 2 pcs CR123A Lithium batteries.
- Multi color lights combination for various scenarios
- Anti-vibration design
- ► Micro-USB charging port, 5V/1A charging
- ► Hard anodizing aircraft grade aluminum alloy

FL1 Standard	High	Mid	Low	Eco	Red light	Green light	Blue light
ZINE	1000LM	350LM	190LM	9LM	90LM	170LM	50LM
(S)	2.3h	4.5h	10h	180h	4.5h	4.2h	5.3h
<u> </u>	160g/ 5.64oz (without battery) 208g/ 7.34oz (with battery)						
Imimimimi	148mm x 38mm 5.83in x 1.50in (L x D)						























IR Flashlight

- Utilized 1*CREE XP-L white light LED, 2*OSRAM IR LEDs(850nm or 940nm)
- ► Powered by 1 pcs 18650 Li-ion battery, compatible with 2 pcs CR123A Lithium batteries.
- ► Night vision assistant lighting(used with night vision equipment)
- ► Anti-vibration design
- ► Micro-USB charging port, 5V/1A charging
- ► Hard anodizing aircraft grade aluminum alloy

FL1 Standard	High	Mid	Low	IR		
ZINE	1000LM	500LM	10LM	3500mW		
O	3.7h	4.6h	200h	3.5h		
△1	140g/ 4.94oz (without battery) 188g/ 6.63oz (with battery)					
Iminimimi	131mm x 37mm 5.16in x 1.46in (L x D)					

-	122m











PRODUCT SERIES

TACTICAL

P45R Handheld Tactical Flashlight





- ▶ 2000 lumens max output
- ▶ 370 meters max beam distance
- ▶ Powered by 1 pcs 18650 high-drain Li-ion battery
- Intelligent battery power indication
- ▶ Built-in Micro-USB charging port, 5V/1A charging
- ► Hard anodizing aircraft grade aluminum alloy

FL1 Standard	Turbo	High	Mid	Low	SOS	Strobe	
714	2000 ~700 LM	500LM	130LM	10LM	200LM	2000LM	
()	3+90 mins	3h	8h	40h	/	/	
△1△	142g/ 5.01	142g/ 5.01oz (without battery) 191g/ 6.74oz (with battery)					
Imhahahal	162.6mm	162.6mm x 37mm 6.40in x 1.46in (L x D)					

Cool white





Интернет-магазин светодиодных фонарей








outdoor









T70

Camping Flashlight

- ► Utilized 1*CREE XHP70.2 LED
- ► Powered by 1 pcs 26650 high-drain Li-ion battery
- ▶ 4200 lumens max output
- 250 meters max beam distance
- ► Built-in Type-C charging port, 5V/2A charging
- ► Hard anodizing aircraft grade aluminum alloy

	FL1 Standard	Turbo	High	Mid	Low		
	31/5	4200\1300\500 LM	1300 ∿ 500 LM	400LM	40LM		
	0	1+60+60 mins	2.5h	7.5h	35h		
	<u> </u>	164g/ 5.78oz (without battery) 261g/ 9.21oz (with battery)					
139.7mm x 42mm 5.5in x 1.65in (L x D)							





















T101 Pro

Searching Flashlight

- ► Utilized 1*CREE XHP70.2 LED
- ► Powered by 2 pcs 18650 high-drain Li-ion batteries
- ▶ 3500 lumens max output
- 500 meters max beam distance
- ► Type-C charging port, 5V/2A charging
- Hard anodizing aircraft grade aluminum alloy

FL1 Standard	Turbo	High	Mid	Low	Eco	
3115	3500 ∖1500 LM	1250LM	450LM	100LM	10LM	
O	3+79 mins	3h	6h	29.2h	290h	
<u> </u>	367g/ 12.95oz (without battery) 463g/ 16.33oz (with battery)					
[m]m m m m]	259mm x 65mm 10.20in x 2.56in (L x D)					























T102 Pro

Searching and Rescuing Flashlight

- ► Utilized 1*CREE XHP70.2 LED
- ▶ Powered by 1 pcs 26650 high-drain Li-ion battery
- ▶ 3500 lumens max output
- ▶ 500 meters max beam distance
- ► Built-in Type-C charging port, 5V/2A charging
- ► Hard anodizing aircraft grade aluminum alloy

FL1 Standard	Turbo	High	Mid	Low
ZINE	3500LM	800LM	200LM	10LM
(1.5h	3.3h	14h	240h
<u> 4</u>	325g/ 11.46oz (without battery) 421g/ 14.85oz (with battery)			
Imhaladadad	191mm x 65mm I 7.52in x 2.56in (L x D)			





















T103 Pro

Patrolling Flashlight

- ► Utilized 1*CREE XHP35 LED
- ► Powered by 1 pcs 18650 high-drain Li-ion battery
- ▶ 1280 lumens max output
- 508 meters max beam distance
- ► Built-in Type-C charging port, 5V/2A charging
- ► Hard anodizing aircraft grade aluminum alloy

FL1 Standard	Turbo	High	Mid	Low	Eco
Zink	1280LM	500LM	200LM	40LM	5LM
()	1.2h	2.1h	7h	34h	340h
414	177g/ 6.24oz (without battery) 224g/ 7.90oz (with battery)				
Imhahahal	172mm x 42mm 6.77in x 1.65in (L x D)				





















T105 Pro

Patrolling Flashlight

- ► Utilized 1*CREE XHP35 LED
- ► Powered by 1 pcs 26650 high-drain Li-ion battery
- ▶ 1500 lumens max output
- ▶ 732 meters max beam distance
- ► Built-in Type-C charging port, 5V/2A charging
- ► Hard anodizing aircraft grade aluminum alloy

FL1 Standard	Turbo	High	Mid	Low	Eco
ZINE	1500LM	550LM	200LM	50LM	10LM
Q	2.3h	4h	11.3h	50h	200h
<u> 4</u>	325g/ 11.46oz (without battery) 421g/ 14.85oz (with battery)				
Iminimimimi	207mm x 57.5mm 8.15in x 2.26in (L x D)				

/_	1 x CR XHP35













KUPIFINARIKZ











A21

Vehicle Flashlight

- ► Utilized 1*CREE XHP70.2 LED
- ► 4200 lumens max output
- ▶ 227 meters max beam distance
- ▶ Powered by 1 pcs 21700 high-drain Li-ion battery
- ► Built-in Type-C charging port, 5V/2A charging
- ► Intelligent battery power indication
- ► Hard anodizing aircraft grade aluminum alloy

FL1 Standard	Turbo	High	Mid	Low	Moon
ZINE	4200LM	1200LM	400LM	130LM	5LM
(S)	2h	4.5h	8.5h	20h	110h
<u> </u>	147g/ 5.19oz (without battery) 218g/ 7.69oz (with battery)				
Imimimimi	135.5mm x 42mm 5.33in x 1.65in (L x D)				

1 x CREE
XHP70.2 LED























TP10

Tactical Pen

- ▶ 3 in 1 tactical pen
- ► Utilized 1*CREE XP-G2 LED
- ▶ Powered by 1 pcs built-in 10180 Li-ion battery
- ▶ Rechargeable light head with 130 lumens max output
- ► German refill for smooth writing
- ► Super hard tungsten steel striker to deal with emergencies
- ► Hard anodizing aircraft grade aluminum alloy

	FL1 Standard	High	Low	
;	ZINE	130LM	3LM	
	(40mins	6h	
	<u> 4</u>	40g/ 1.41oz (with battery)		
153.5mm x 13.5mm l 6.04in x 0.53in (L x D)				





















TP10-G

Tactical Pen

- ▶ 3 in 1 tactical pen
- ▶ Utilized 1 pcs 3535 LED
- ▶ Powered by 1 pcs built-in 10180 Li-ion battery
- ▶ Rechargeable light head with 130 lumens max output
- Refill with smooth writing
- ► Super hard tungsten steel striker to deal with emergencies
- ► Hard anodizing aircraft grade aluminum alloy

FL1 Standard	High	Low		
Zytz	130LM	3LM		
O	22mins	11h		
△1△				
Imminimi	154mm x 13.8mm 6.06in x 0.54in (L x D)			























P26 UV Flashlight

- ▶ White and UV dual light sources
- ▶ Utilized 1*CREE XPG3 white light LED, and 1*365nm UV LED
- ► Powered by 3 pcs AAA batteries, compatible with 1 pcs 18650 Li-ion battery
- ▶ 500 lumens max output
- Dual individual control switches
- ► Hard anodizing aircraft grade aluminum alloy

Light color	ht color White light		UV light
FL1 Standard	High	Low	/
ANT	500LM	150LM	365nm/2W
Q	/	6.5h	5.5h
△]△	117g/ 4.13oz (without battery) 145g/ 5.11oz (with battery)		
haladadadad	130mm x 40mm 5.12in x 1.57in (L x D)		























E05

EDC Flashlight

- ► Utilized 1*CREE XPL LED
- ▶ 900 lumens max output
- ▶ 130 meters max beam distance
- ▶ 14500 Li-ion battery with Micro-USB charging port
- ► Side switch
- Magnetic tailcap
- ► Double-way clip
- Intelligent battery power indication



FL1 Standard	Turbo	High	Mid	Low	Strobe	SOS	
Zyn.F	900 ~ 300 LM	150LM	30LM	1LM	150LM	150LM	
O	3+60 mins	3h	11h	115h	/	/	
∆[∆	40g/ 1.41oz (without battery) 60g/ 2.12oz (with battery)						
Imhahaladad	88mm x 23	3.46in	x 0.91in (L x 🛭))			

\sim	1 x CREE
	XPL LED





















E01

EDC Flashlight

- ► Utilized 1*CREE XPG3 LED
- ► Powered by 1 pcs AAA battery
- ▶ 100 lumens max output
- 40 meters max beam distance
- ► Tail switch
- ► Hard anodizing aircraft grade aluminum alloy

FL1 Standa	ard High	Mid	Low	SOS				
3115	100LM	20LM	1LM	20LM				
O	50mins	6.5h	50h	/				
△]△	18g/ 0.63oz (with	18g/ 0.63oz (without battery) 29g/ 1.02oz (with battery)						
Imimimimi	82.5mm x 15mm	l 3.25in x 0.59in (L x	D)					

























E10

EDC Flashlight

- ▶ Utilized 1*OSRAM P9 LED
- ► Powered by 1 pcs 18650 Li-ion battery, compatible with 2 pcs CR123A Lithium batteries
- ▶ 1200 lumens max output
- ▶ Compact and portable size
- Low power warning
- ► Intelligent battery power indication
- ► Hard anodizing aircraft grade aluminum alloy

FL1 Standard	Turbo	High	Mid	Low	Strobe	SOS	
3,1,5	1200 ∿ 700 LM	300LM	100LM	1LM	1200LM	200LM	
0	1+110 mins	6.5h	21h	514h	/	/	
<u> </u>	76g/ 2.68oz (without battery) 123g/ 4.34oz (with battery) 124.2mm x 25.4mm 4.89in x 1in (L x D)						
Imhahahala							

P9 LED	_	1 x OSRAM P9 LED
--------	---	---------------------





















Outdoor Flashlight

- ► Utilized 1*OSRAM P9 LED
- ► 1200 lumens max output
- ▶ 200 meters max beam distance
- ► Powered by 1 pcs 18650 Li-ion battery, compatible with 2 pcs CR123A Lithium batteries
- ► Built-in Micro-USB charging port, 5V/1A charging
- ► Intelligent battery power indication
- Anti-reverse battery installation protection
- Intelligent temperature control
- ► Low power warning
- Hard anodizing aircraft grade aluminum alloy

FL1 Standard	High	Mid	Low	Eco	SOS		
3115	1200LM	400LM	75LM	5LM	200LM		
O	1.5h	2.5h	8.5h	143h	/		
ΔĪΔ	96g/ 3.39oz (without battery) 143g/ 5.04oz (with battery) 138.6mm x 26mm 5.46in x 1.02in (L x D)						
lmlmlmlml							





















LT35

Zoomable Flashlight

- ► Utilized 1*CREE XPL LED
- ► Powered by 1 pcs 18650 Li-ion battery, compatible with 2 pcs CR123A Lithium batteries
- ▶ 1200 lumens max output
- ▶ 320 meters max beam distance
- ► Built-in Micro-USB charging port, 5V/1A charging
- ► Low power warning

F	L1 Standard	High	Mid	Low	Eco	SOS			
	ZINE	1200LM	350LM	70LM	5LM	200LM			
	()	1.8h	3h	15.4h	218.8h	/			
	414	128g/ 4.52oz (without battery) 175g/ 6.17oz (with battery)							
	Imminimini	148mm x 39mm I 5.83in x 1.54in (L x D)							

_	1 x CREE
	XPL LED

















Outdoor Flashlight

- ► Utilized 1*CREE XPL-V6 LED
- ▶ Powered by 1 pcs 18650 Li-ion battery, compatible with 2 pcs CR123A Lithium batteries
- ► 1200 lumens max output
- ▶ 220 meters max beam distance
- Dual side switches
- ► Intelligent battery power indication
- ► Instant Turbo
- Instant Strobe
- Built-in Micro-USB charging port, 5V/1A charging
- Hard anodizing aircraft grade aluminum alloy





FL1 Standard	Turbo	High	Mid	Low	Moon		
31/5	1200∿700LM	600LM	200LM	40LM	8LM		
0	3+105mins	3.5h	7h	56h	125h		
া ত	93g/ 3.28oz (without battery) 141g/ 4.97oz (with battery)						
Imimimimi	130.2mm x 25.4mm 5.13in x 1.00in (L x D)						





















TO50R

Outdoor Flashlight

- ► Utilized 4*SAMSUNG LH351D high CRI value LEDs
- ► Powered by 1 pcs 21700 Li-ion battery, compatible with 1 pcs 18650 Li-ion battery
- ► 2800 lumens max output
- ► Instant Turbo
- ► Instant Strobe
- Dual side switches
- Power bank function(5V/2A output)
- ► Built-in Micro-USB charging port, 5V/2A charging

FL1 Standard	Turbo	High	Mid	Low	Micro	Moon		
31/5	2800LM	1250LM	250LM	50LM	10LM	1LM		
Q	1.7h	3.5h	7h	56h	125h	/		
₹	130g/ 4.59	130g/ 4.59oz (without battery) 202g/ 7.13oz (with battery)						
[minimum]	124.5mm	x 31mm 4.90)in x 1.22in (L	x D)				























TO46R

High CRI Value Flashlight

- ▶ Utilized 3*NICHIA 219C high CRI value LEDs
- ▶ Powered by 1 pcs 18650 Li-ion battery
- ▶ 1100 lumens max output
- Dual side switches
- ► Intelligent battery power indication
- ► Instant Turbo
- ► Instant Strobe
- ► Built-in Micro-USB charging port, 5V/1A charging
- ► Hard anodizing aircraft grade aluminum alloy

	FL1 Standard	Turbo	High	Mid	Low	Moon				
	Zint.	1100LM	200LM	40LM	5LM					
	(S)	1.7h	3.5h	7h	56h	125h				
81g/ 2.86oz (without battery) 128g/ 4.52oz (with battery)										
		120mm x 26r	120mm x 26mm 4.72in x 1.02in (L x D)							





















TO10R

Photographing Assistant Lighting Flashlight

- ► Utilized 3*NICHIA 219C High CRI value LEDs
- ► Powered by 1 pcs 16340 Li-ion battery, compatible with 1 pcs 18350 Li-ion battery
- ► 800 lumens max output
- Dual side switches
- ► Intelligent battery power indication
- ► Magnetic tailcap
- ► Instant Strobe
- ► Built-in Micro-USB charging port, 5V/1A charging
- Hard anodizing aircraft grade aluminum alloy

	FL1 Standard	High	Mid	Low	Moon	Strobe	SOS		
	ANE	800LM	200LM	40LM	5LM	800LM	800LM		
7	()	1h	3.2h	12h	60h	/	/		
	Δ] Δ	46g/ 1.62oz (without battery) 93g/ 3.28oz (with battery)							
	Imimimimi	86.1mm x 26mm 3.39in x 1.02in (L x D)							





OUTDOOR



- Utilized 1*CREE XPL-V5 LED
- ▶ 1100 lumens max output
- ▶ 283 meters max beam distance, 325 hours max runtime
- ▶ Powered by 1 pcs 18650 Li-ion battery
- ► Micro-USB charging port, 5V/1A charging
- ► Dimension: 158mm x 31mm(L x D), Weight: 140g(without battery)

1331



- Utilized 1*CREE XPL-V5 LED
- ▶ 520 lumens max output
- ▶ 100 meters max beam distance, 90 hours max runtime
- ► Powered by 1 pcs 14500 Li-ion battery
- Micro-USB charging port, 5V/1A charging
- ▶ Dimension: 125mm x 26mm(L x D), Weight: 85.8g(without battery)

1332



- ► Utilized 1*CREE XPL-V5 LED
- ▶ 520 lumens max output
- ▶ 190 meters max beam distance, 100 hours max runtime
- ▶ Powered by 1 pcs 16340 Li-ion battery
- Micro-USB charging port, 5V/1A charging
- ► Dimension: 112mm x 27mm(L x D), Weight: 86g(without battery)

1330



- ► Utilized 1*CREE XPL-V5 LED
- ▶ 450 lumens max output
- ▶ 100 meters max beam distance, 90 hours max runtime
- ► Powered by 1 pcs 10440 Li-ion battery
- Micro-USB charging port, 5V/1A charging
- Dimension: 106mm x 17.5mm(L x D), Weight: 45g(without battery)

Интернет-магазин светодиодных фонарей



Cool white

E345/E346/E347







FL1 Standard	High	Low		
July 1	300LM 25LM			
(S)	1.2h 11.5h			
△]△	44g/ 1.55oz (with battery)			
Imfinimimi	71.5mm x 21mm 2.81in x 0.83in (L x D)			

1*16340 battery

FL1 Standard	High	Low		
ZINE	260LM 20LM			
O	1.3h 11.5h			
△ [△	38.4g/ 1.35oz (with battery)			
Imhahahalad	82.5mm x 18mm 3.25in x 0.71in (L x D)			

1.5m

IPX8

1*14500 battery



Cool white

Micro-USB charging

E348/E349/E350

IPX8



E501/E502/E503

1 x CREE XP-G2 LED



Micro-USB charging

FL1 Standard	High		Low	
3,1,5	150LM	3/\	10LM	
(S)	50mins	A	11h	
△ [△	25.4g/ 0.90oz (with battery)	5		
Imindulmimi	76.2mm x 14.7mm I 3in x 0.58in (L >	(D)		D
1 x CREE	Micro-USB 1*10440	1.5m 🔄	~ IPX8 I ≪	Cool white



G339

G342



G337
Titanium alloy

\$\alpha \text{41mm x 13.5mm(L x D)}

22.4g(with battery)



G338
Titanium alloy

△T△ 43.5mm x 13.5mm(L x D)

= 21.6q(with battery)



Stainless steel

41mm x 13.5mm(L x D)

28.8q(with battery)



Stainless steel
43.5mm x 13.5mm(L x D)
28.4g(with battery)



G341



Aluminum alloy

41mm x 13.5mm(L x D)

19g(with battery)



G343
Aluminum alloy

△T△ 43mm x 13.5mm(L x D)

18.2g(with battery)



G344
Aluminum alloy

△↑△ 43mm x 13.5mm(L x D)

18.2g(with battery)

FL1 Standard	High	Low
311/2	130LM	3LM
O	40mins	6h

1 x CREE XP-G2 LED Micro-USI charging

1*10 bat

1.5m

5m 🕌

Cool white



PRODUCT

MODEL	MAX OUTPUT	MAX RUNTIME	LED	TINT	BEAM DISTANCE
T32	1200 lumens	530h	CREE XP-L2 LED	Cool white	230m
T20	1100 lumens	3h	CREE XP-L2 LED	Cool white	162m
H8	1800 lumens	468h	CREE XHP35 HI LED	Cool white	1000m
Н9	10 mW	6h	OSRAM 520nm green laser module	Cool white	1035m
T31	1000 lumens	180h	CREE XP-L LED / CREE XP-E Red LED CREE XP-E Green LED / CREE XP-E Blue LED	Cool white	125m
T30	1000 lumens	200h	CREE XP- L LED / OSRAM 850nm / 940nm LED	Cool white	122m
P45R	2000 lumens	40h	CREE XHP35 LED	Cool white	370m
AP10	/	/	/	/	/
T70	4200 lumens	35h	CREE XHP70.2 LED	Cool white	250m
T101 Pro	3500 lumens	290h	CREE XHP70.2 LED	Cool white	500m
T102 Pro	3500 lumens	240h	CREE XHP70.2 LED	Cool white	500m
T103 Pro	1280 lumens	340h	CREE XHP35 LED	Cool white	508m
T105 Pro	1500 lumens	200h	CREE XHP35 LED	Cool white	732m
A21	4200 lumens	110h	CREE XHP70.2 LED	Cool white	227m
TP10	130 lumens	6h	CREE XP-G2 LED	Cool white	60m
TP10-G	130 lumens	11h	3535 LED	Cool white	60m
P26	500 lumens	6.5h	CREE XPG3 LED/365nm UV LED	Cool white	150m
E05	900 lumens	115h	CREE XPL LED	Cool white	130m
E01	100 lumens	50h	CREE XPG3 LED	Cool white	40m
E10	1200 lumens	514h	OSRAM P9 LED	Cool white	215m
L50	1200 lumens	143h	OSRAM P9 LED	Cool white	200m
LT35	1200 lumens	218.8h	CREE XPL LED	Cool white	320m
T040R	1200 lumens	125h	CREE XPL-V6 LED	Cool white	220m
T050R	2800 lumens	-125h	SAMSUNG LH351D high CRI value LED	Warm light	135m

BATTERY TYPE	CHARGING	DIMENSION (LxD)	WEIGHT(without battery)	WATERPROOF LEVEL	PAGE
1*18650/ 2*CR123A	/	144mm x 38mm	140g	IP68	04
1*CR123A	/	85mm x 34.5mm	96g	IP68	06
2*18650	/	250mm x 63mm	298g	IP68	08
1*18650	/	191mm x 35mm	128g	IP66	10
1*18650	Micro-USB charging	148mm x 38mm	160g	IP68	12
1*18650	Micro-USB charging	131mm x 37mm	140g	IP68	14
1*18650	Micro-USB charging	162.6mm x 37mm	142g	IP68	15
/	/	/	128g	IP68	16
1*26650	TYPE-C charging	139.7mm x 42mm	164g	IP68	18
2*18650	TYPE-C charging	259mm x 65mm	367g	IP68	20
1*26650	TYPE-C charging	191mm x 65mm	325g	IP68	22
1*18650	TYPE-C charging	172mm x 42mm	177g	IP68	24
1*26650	TYPE-C charging	207mm x 57.5mm	325g	IP68	26
1*21700	TYPE-C charging	135.5mm x 42mm	147g	IP68	28
1*10180	Micro-USB charging	153.5mm x 13.5mm	40g(with battery)	IP68	30
1*10180	Micro-USB charging	154mm x 13.8mm	41g(with battery)	IP68	32
3*AAA/ 1*18650	1	130mm x 40mm	117g	IP68	34
1*14500/ 1*AA	Micro-USB charging	88mm x 23mm	40g	IP68	36
1*AAA		82.5mm x 15mm	18g	IP68	38
1*18650/ 2*CR123A	A	124.2mm x 25.4mm	76g	IP68	40
1*18650/ 2*CR123A	Micro-USB charging	138.6mm x 26mm	96g	IP68	42
1*18650/ 2*CR123A	Micro-USB charging	148mm x 39mm	128g	IP68	44
1*18650/ 2*CR123A	Micro-USB charging	130.2mm x 25.4mm	93g	IP68	46
1*21700/ 1*18650	Micro-USB charging	124.5mm x 31mm	130g	IP68	48

Интернет-магазин светодиодных фонарей

SPECIFICATIONS

PRODUCT

MODEL	MAX OUTPUT	MAX RUNTIME	LED	TINT	BEAM DISTANCE
TO46R	1100 lumens	125h	NICHIA 219C high CRI value LED	Warm light	135m
TO10R	800 lumens	60h	NICHIA 219C High CRI value LED	Warm light	800m
1330	450 lumens	90h	CREE XPL-V5 LED	Cool white	100m
I331	520 lumens	90h	CREE XPL-V5 LED	Cool white	100m
1332	520 lumens	100h	CREE XPL-V5 LED	Cool white	190m
1333	1100 lumens	325h	CREE XPL-V5 LED	Cool white	283m
E345	300 lumens	11.5h	CREE XP-G2 LED	Cool white	120m
E346	300 lumens	11.5h	CREE XP-G2 LED	Cool white	120m
E347	300 lumens	11.5h	CREE XP-G2 LED	Cool white	120m
E348	260 lumens	11.5h	CREE XP-G2 LED	Cool white	100m
E349	260 lumens	11.5h	CREE XP-G2 LED	Cool white	100m
E350	260 lumens	11.5h	CREE XP-G2 LED	Cool white	100m
E501	150 lumens	11h	CREE XP-G2 LED	Cool white	60m
E502	150 lumens	11h	CREE XP-G2 LED	Cool white	60m
E503	150 lumens	11h	CREE XP-G2 LED	Cool white	60m
G337	130 lumens	6h	CREE XP-G2 LED	Cool white	60m
G338	130 lumens	6h	CREE XP-G2 LED	Cool white	60m
G339	130 lumens	6h	CREE XP-G2 LED	Cool white	60m
G340	130 lumens	6h	CREE XP-G2 LED	Cool white	60m
G341	130 lumens	6h	CREE XP-G2 LED	Cool white	60m
G342	130 lumens	6h	CREE XP-G2 LED	Cool white	60m
G343	130 lumens	6h	CREE XP-G2 LED	Cool white	60m
G344	130 lumens	6h	CREE XP-G2 LED	Cool white	60m

All parameters above are from WUBEN experiments, parameters may vary if products upgrading, please refer to the product user manual for exact product informations. Final interpretation right reserved by WUBEN.

BATTERY TYPE	CHARGING	DIMENSION (LxD)	WEIGHT	WATERPROOF LEVEL	PAGE
1*18650/ 2*CR123A	Micro-USB charging	120mm x 26mm	81g	IP68	50
1*16340/ 1*18350	Micro-USB charging	86.1mm x 26mm	46g	IP68	52
1*10440	Micro-USB charging	106mm x 17.5mm	45g(without battery)	IPX8	54
1*14500	Micro-USB charging	125mm x 26mm	85.8g(without battery)	IPX8	54
1*16340	Micro-USB charging	112.5mm x 27mm	86g(without battery)	IPX8	54
1*18650	Micro-USB charging	158.7mm x 31.5mm	140g(without battery)	IPX8	54
1*16340	Micro-USB charging	71.5mm x 21mm	44g(with battery)	IPX8	56
1*16340	Micro-USB charging	71.5mm x 21mm	44g(with battery)	IPX8	56
1*16340	Micro-USB charging	71.5mm x 21mm	44g(with battery)	IPX8	56
1*14500	Micro-USB charging	82.5mm x 18mm	38.4g(with battery)	IPX8	56
1*14500	Micro-USB charging	82.5mm x 18mm	38.4g(with battery)	IPX8	56
1*14500	Micro-USB charging	82.5mm x 18mm	38.4g(with battery)	IPX8	56
1*10440	Micro-USB charging	76.2mm x 14.7mm	25.4g(with battery)	IPX8	56
1*10440	Micro-USB charging	76.2mm x 14.7mm	25.4g(with battery)	IPX8	56
1*10440	Micro-USB charging	76.2mm x 14.7mm	25.4g(with battery)	IPX8	56
1*10180	Micro-USB charging	41mm x 13.5mm	22.4g(with battery)	IPX8	58
1*10180	Micro-USB charging	43.5mm x 13.5mm	21.6g(with battery)	IPX8	58
1*10180	Micro-USB charging	41mm x 13.5mm	28.8g(with battery)	IPX8	58
1*10180	Micro-USB charging	43.5mm x 13.5mm	28.4g(with battery)	IPX8	58
1*10180	Micro-USB charging	41mm x 13.5mm	19g(with battery)	IPX8	58
1*10180	Micro-USB charging	41mm x 13.5mm	19g(with battery)	IPX8	58
1*10180	Micro-USB charging	43.5mm x 13.5mm	18.2g(with battery)	IPX8	58
1*10180	Micro-USB charging	43.5mm x 13.5mm	18.2g(with battery)	IPX8	58







Wuben Lights 2019

Официальный представитель в Республике Казахстан -интернет-магазин KupiFonar.kz 050000, ул.Щепеткова 117, офис 3, г.Алматы, Республика Казахстан 8 (727) 249 67 70 +7-777-8202999 info@kupifonar.kz www.kupifonar.kz